
TLGDL3R6AWH

Gimbal LED recessed light





Specifications TLGDL3R6AWH

Electrical Specifications	
Model No.	TLGDL3R6AWH
Power (W) ± 10%	6 W
Input Voltage (V)	AC120 V, 60Hz
Efficacy ± 3%	2700K: 80.33 lm/W 3000K: 85.7 lm/W 3500K: 91 lm/W 4000K: 100.17 lm/W 5000K: 96 lm/W
Power Factor (PF)	>0.9
Dimmable	Triac

Photometric Specifications	
CRI	90
CCT	Selectable
Beam angle	36°
Light Output ± 3%	2700K: 482 lm 3000K: 514 lm 3500K: 546 lm 4000K: 601 lm 5000K: 576 lm

Mechanical Specifications	
IP Rating	Wet locations
Material	Aluminum + Metal box
Lens	Frosted (Polycarbonate)
Net Weight	N/A
Product size (mm)	± Ø100 x 29.29 mm
Product size (in)	± Ø3.94" x 1.15"
Operating Humidity	10% ~ 90%
Operating Temperature	-30°C ~ 45°C
Lumen maintenance	N/A


Product Description:

- 3" recessed down light.
- Adjustable light direction (up to 90°).
- Type IC.
- Airtight according to ASTM E283-04.
- Junction box with quick connector included.
- 5 CCT: selectable 2 700 K, 3 000 K, 3 500 K, 4 000 K and 5 000 K using a switch.
- No toxic chemicals, RoHS compliant.
- Color: white.
- Optional installation plate.

Applications:

Houses, schools, shopping centers, etc.

Accessory (not included)



TLMP36HB
3" to 6" mounting plate with fixing bars

info@technilight.ca

Pictures for illustration purpose only rev 2.6.4