
TLSPU60045PBK IP65





Specifications TLSPU60045PBK

Electrical Specifications	
Model No.	TLSPU60045PBK
Power (W) ± 10%	600 W
Input Voltage (V)	AC120-347V, 50/60Hz
Efficacy ± 3%	140 lm/W
Power Factor (PF)	0.9
Surge protection	10 kv
Total harmonic distortion	N/A

Photometric Specifications	
CRI	75
CCT	5 000 K
Beam angle	45°
Light Output ± 3%	84 000 lm
Dimmable	0-10 V

Mechanical Specifications	
IP Rating	IP65
Vibration rating	3G
EPA	1.57 pi^2
Material	Aluminum
Lens	PC
Net Weight	10 kg
Product size (mm)	Ø361 x 324 x 409 mm
Product size (inch)	Ø14.2 x 12.8 x 16.1"
Operating Humidity	10% - 90%
Operating Temperature	-40°C ~ 50°C

Product description:

- Robust and solid, the design provides excellent heat dissipation, ensuring stability and longer life expectancy.
- Available in multiple beam angles for narrow projection.
- Economy on electricity consumption compared to traditional lighting fixture.
- Other CCT available on special request.
- Warranty: 5 years.
- Also available: 15°, 30° and 60°.

Applications:

Flood light.
Stadiums, race track, playgrounds, large area parkings, construction sites, etc.

Accessories not included



TLSPSFBK
«Slip fitter» bracket



TLSPLAD
Laser aiming device

info@technilight.ca

Pictures for illustration purpose only