TLTFUS14W50AD IP20





Specifications TLTFUS14W50AD

Electrical specifications	
Model No.	TLTFUS14W50AD
DLC ID	N/D
Selectable power (W) ± 10%	15W / 20W / 30W / 40W / 50W
Input Voltage (V)	AC 120-347V, 50/60Hz
Efficacy ± 3%	125 lm/W
Power Factor (PF)	0.9
Surge protection	N/D
Total harmonic distortion	<15%

Photometric specifications	
CRI	80
CCT selectable	30K / 35K / 40K / 45K / 50K
Beam angle	120°
Light Output ± 3%	Min: 1 875 lm Max: 6 250 lm
Dimmable	0-10V

Mechanical specifications	
IP Rating	IP20 / Damp locations
Material	SPCC + PC
Lens	Frosted
Net Weight	5.2 kg
Product size (mm)	± 1194 x 280 x 50 mm
Product size (inch)	± 47.7" x 11.8" x 2"
Operating Humidity	10% - 90%
Operating Temperature	-40°C ~ 50°C
Lumen maintenance	>82% at 100 000 hours

Product description:

- Large supply voltage range 120-347V.
- Selectable power and CCT.
- Versatile design makes installation easy which reduces installation time and costs.
- Saves on electricity consumption compared to fluorescent lighting fixture.
- Warranty: 5 years.
- High efficiency reflective PC cover, soft and bright lighting.

Applications:

Suitable for offices, conference rooms, shops, supermarkets, etc.

Optional accessories

		
Surface insallation frame 1' x 4' white	Recessed mounting frame 1' x 4' white	Emergency battery
TLPBL14WMF	**TLPL14RMFWH**	**BLD-HM15D**

info@technilight.ca

Pictures for illustration purpose only

rev 2.6.3