
TLTFUS22W40AD IP20





Specifications TLTFUS22W40AD

Electrical specifications	
Model No.	TLTFUS22W40AD
DLC ID	S-RNPXVC
Adjustable power (W) ± 10%	20W / 30W / 40W
Input Voltage (V)	AC 120-347V, 50/60Hz
Efficacy ± 3%	127.55 lm/W
Power Factor (PF)	0.951
Surge protection	N/D
Total harmonic distortion	<15%

Photometric specifications		
CRI	84	
Selectable CCT	3500K / 4000K / 5000K	
Beam angle	120°	
Light Output ± 3%	20W: 2551 lm	30W: 3827 lm
	40W: 5102 lm	
Dimmable	0-10V	

Mechanical specifications	
IP Rating	IP20 / Damp locations
Material	SPCC + PC
Lens	Frosted
Net Weight	5.2 kg
Product size (mm)	± 603 x 603 x 50 mm
Product size (inch)	± 24" x 24" x 2"
Operating Humidity	10% - 90%
Operating Temperature	-40°C ~ 50°C
Lumen maintenance	>77% at 100 000 hours

Product description:

- Large supply voltage range 120-347V.
- Selectable power and CCT.
- Versatile design makes installation easy which reduces installation time and costs.
- Saves on electricity consumption compared to fluorescent lighting fixture.
- Warranty: 5 years.
- High efficiency reflective PC cover, soft and bright lighting.

Applications:

Suitable for offices, conference rooms, shops, supermarkets, etc.

Optional accessories

		
Surface insallation frame 2' x 2' white	Recessed mounting frame 2' x 2' white	Emergency battery
TLPBL22WMF	TLPL22RMFWH	BLD-HM08D

info@technilight.ca

Pictures for illustration purpose only