
TLWMO12PDB IP65





Specifications TLWMO12PDB

Electrical Specifications	
Model No.	TLWMO12PDB
DLC ID	N/D
Power (W) ± 10%	12 W
Input Voltage (V)	AC 120-277V, 50/60Hz
Efficacy ± 3%	85 lm/W
Power Factor (PF)	0.9
Surge protection	N/D
Total harmonic distortion	N/D

Photometric Specifications	
CRI	≥80
CCT	5 000 K
Beam angle	N/D
Light Output ± 3%	1 020 lm
Dimmable	No

Mechanical Specifications	
IP Rating	IP65
Material	Aluminum
Lens	Clear (PC)
Net Weight	N/D
Product size (mm)	160 x 265 x 98 mm
Product size (inch)	± 6.3" x 10.4" x 3.86"
Operating Humidity	10% - 90%
Operating Temperature	-25°C ~ 40°C

Product Description:

- Die cast aluminum housing provides solid mounting to wall.
- Photocell included. ON / OFF selectable.
- Emergency battery included. (Use above 0°C).
- Saves on electricity consumption compared to conventional lighting fixture.
- Color: bronze.
  Other colors available on special request.
- Warranty: 5 Years.

Applications:

Perimeter lighting for safety and security. Use on factories, warehouses, commercial buildings, hotels, etc.

info@technilight.ca

Pictures for illustration purpose only

rev 2.5.11